

|          |                                      | ENGLISH (inches)                                    |    |   |    |
|----------|--------------------------------------|---|----|---|----|
| Bar Size | Pavement Thickness                   | (Approx. Spacing)                                   | B  | © | 0  |
| #6       | $7\frac{3}{4}$ thru $8\frac{1}{2}$   | 18 spaces (19 bars) @ 7 <sup>5</sup> / <sub>8</sub> | 3½ | 3 | 22 |
| #6       | $8\frac{3}{4}$ thru $9\frac{1}{2}$   | 20 spaces (21 bars) @ 6\%                           | 3½ | 3 | 22 |
| #6       | $9\frac{3}{4}$ thru $10\frac{1}{2}$  | 22 spaces (23 bars) @ 6 <sup>1</sup> / <sub>4</sub> | 3½ | 3 | 22 |
| #6       | $10\frac{3}{4}$ thru $11\frac{1}{2}$ | 24 spaces (25 bars) @ 5¾                            | 3½ | 3 | 22 |
| #6       | $11\frac{3}{4}$ thru $12\frac{1}{2}$ | 27 spaces (28 bars) @ 51/8                          | 3½ | 3 | 22 |
| #7       | $9\frac{3}{4}$ thru $10\frac{1}{2}$  | 16 spaces (17 bars) @ 85%                           | 3½ | 3 | 26 |
| #7       | $10\frac{3}{4}$ thru $11\frac{1}{2}$ | 18 spaces (19 bars) @ 75/8                          | 3½ | 3 | 26 |
| #7       | 11¾ thru 12½                         | 19 spaces (20 bars) @ 71/4                          | 3½ | 3 | 26 |
| #7       | $12\frac{3}{4}$ thru $13\frac{1}{2}$ | 21 spaces (22 bars) @ 6½                            | 3½ | 3 | 26 |
| #7       | $13\frac{3}{4}$ thru $14\frac{1}{2}$ | 23 spaces (24 bars) @ 6                             | 3½ | 3 | 26 |
| #7       | $14\frac{3}{4}$ thru $15\frac{1}{2}$ | 24 spaces (25 bars) @ 5¾                            | 3½ | 3 | 26 |
| #7       | $15\frac{3}{4}$ thru $16\frac{1}{2}$ | 26 spaces (27 bars) @ 51/4                          | 3½ | 3 | 26 |

|          |                    | METRIC (mm)               |    |    |     |
|----------|--------------------|---------------------------|----|----|-----|
| Bar Size | Pavement Thickness | (Approx. Spacing)         | B  | ©  | (D) |
| #19      | 200 thru 220       | 18 spaces (19 bars) @ 191 | 90 | 75 | 560 |
| #19      | 230 thru 250       | 21 spaces (22 bars) @ 163 | 95 | 80 | 560 |
| #19      | 260 thru 280       | 23 spaces (24 bars) @ 149 | 90 | 80 | 560 |
| #19      | 290 thru 310       | 26 spaces (27 bars) @ 132 | 90 | 75 | 560 |
| #19      | 320 thru 340       | 29 spaces (30 bars) @ 118 | 95 | 80 | 560 |
| #22      | 230 thru 250       | 15 spaces (16 bars) @ 229 | 90 | 75 | 660 |
| #22      | 260 thru 280       | 17 spaces (18 bars) @ 202 | 90 | 75 | 660 |
| #22      | 290 thru 310       | 19 spaces (20 bars) @ 181 | 90 | 70 | 660 |
| #22      | 320 thru 340       | 21 spaces (22 bars) @ 163 | 95 | 80 | 660 |
| #22      | 350 thru 370       | 23 spaces (24 bars) @ 149 | 90 | 80 | 660 |
| #22      | 380 thru 400       | 25 spaces (26 bars) @ 137 | 95 | 80 | 660 |
| #22      | 410 thru 430       | 27 spaces (28 bars) @ 127 | 90 | 80 | 660 |

## **GENERAL NOTES**

Except as noted or shown, the dimensions and notes specified for LAP DETAIL I are typical for LAP DETAIL II and III.

The (B) dimension and the distance from the end of the transverse bar to the edge of pavement may be increased by 1 (25) for slip form paving.

The minimum length of longitudinal bars shall be 30' (9 m) except as required to establish the lap arrangement selected.

All dimensions are in inches (millimeters) unless otherwise shown.

| DATE   | REVISIONS                           |   |
|--------|-------------------------------------|---|
| 4-1-16 | Revised general notes with          |   |
|        | respect to 30' bar length.          |   |
|        |                                     |   |
| 1-1-08 | Switched units to English (metric). | H |
|        |                                     |   |
|        |                                     | 1 |

## BAR REINFORCEMENT FOR CRC PAVEMENT

STANDARD 421001-03